



TP-30 Trough Prefeeder

Designed for Fragile Part Handling

Product Overview

Hoppmann's TP-30 trough prefeeder is specially designed for handling a variety of fragile parts. The prefeeder features protective sides, food grade belt and variable speed control. Designed for floor level parts loading.

Product Specifications

	<u>U.S.</u>	<u>Global</u>
A. Overall Height	62 ±7.5"	1575 ±190mm
B. Overall Width	39"	991mm
C. Overall Length	105"	2667mm
D. Dump Height (Adjustable)	34 ±7.5"	1219 ±190mm
E. Hopper Load Height	62 ±7.5"	1575 ±190mm
F. Belt Width	30"	762mm
Motor Size	1/3 HP	250 W
Motor Frame Size	NEMA 56C	IEC 71D
Supply Voltage	115 VAC	240 VAC
Motor Voltage	90 VDC	180 VDC
Power Usage	5 amps	3 amps
Weight	450 lbs	204 kg
Supply Hopper Capacity	15 ft ³	426 liters



Standard Features

- Mild steel with electrostatic epoxy powder coat finish
- Stainless steel discharge chute, hopper, and sides
- Feeder bowl level sensor
- DC variable speed motor
- FDA approved belt

Standard Options

- Stainless steel construction
- Grated culling chute with catch pan
- Washdown motor

